

# Schottky Diode

## **PBYR1045**

45V / 10A


# DATASHEET

OEM – Philips

Source: Philips Databook 1999

**Rectifier diodes  
Schottky barrier**
**PBYR1045 series**
**FEATURES**

- Low forward volt drop
- Fast switching
- Reverse surge capability
- High thermal cycling performance
- Low thermal resistance

**SYMBOL**

**QUICK REFERENCE DATA**

$$V_R = 40 \text{ V} / 45 \text{ V}$$

$$I_{F(AV)} = 10 \text{ A}$$

$$V_F \leq 0.57 \text{ V}$$


**GENERAL DESCRIPTION**

Schottky rectifier diodes in a plastic envelope. Intended for use as output rectifiers in low voltage, high frequency switched mode power supplies.

The PBYR1045 series is supplied in the conventional leaded SOD59 (TO220AC) package.

**PINNING**

PIN	DESCRIPTION
1	cathode
2	anode
tab	cathode

**SOD59 (TO220AC)**

**LIMITING VALUES**

Limiting values in accordance with the Absolute Maximum System (IEC 134)

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.		UNIT
				PBYR10		
$V_{RRM}$	Peak repetitive reverse voltage		-	40	45	V
$V_{RWM}$	Working peak reverse voltage		-	40	45	V
$V_R$	Continuous reverse voltage	$T_{mb} \leq 113 \text{ }^\circ\text{C}$	-	40	45	V
$I_{F(AV)}$	Average rectified forward current	square wave; $\delta = 0.5$ ; $T_{mb} \leq 136 \text{ }^\circ\text{C}$	-	10		A
$I_{FRM}$	Repetitive peak forward current	square wave; $\delta = 0.5$ ; $T_{mb} \leq 136 \text{ }^\circ\text{C}$	-	20		A
$I_{FSM}$	Non-repetitive peak forward current	$t = 10 \text{ ms}$	-	135		A
		$t = 8.3 \text{ ms}$	-	150		A
$I_{RRM}$	Peak repetitive reverse surge current	sinusoidal; $T_j = 125 \text{ }^\circ\text{C}$ prior to surge; with reapplied $V_{RRM(max)}$ pulse width and repetition rate limited by $T_{jmax}$	-	1		A
$T_j$	Operating junction temperature		-	150		$^\circ\text{C}$
$T_{stg}$	Storage temperature		-65	175		$^\circ\text{C}$

**THERMAL RESISTANCES**

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
$R_{th(j-mb)}$	Thermal resistance junction to mounting base		-	-	2	K/W
$R_{th(j-a)}$	Thermal resistance junction to ambient	in free air	-	60	-	K/W

---

Rectifier diodes  
Schottky barrier

---

PBYR1045 series

**ELECTRICAL CHARACTERISTICS** $T_j = 25\text{ }^{\circ}\text{C}$  unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
$V_F$	Forward voltage	$I_F = 10\text{ A}; T_j = 125\text{ }^{\circ}\text{C}$	-	0.5	0.57	V
		$I_F = 20\text{ A}; T_j = 125\text{ }^{\circ}\text{C}$	-	0.69	0.72	V
		$I_F = 20\text{ A}$	-	0.65	0.84	V
$I_R$	Reverse current	$V_R = V_{RWM}$	-	0.2	1.3	mA
		$V_R = V_{RWM}; T_j = 100\text{ }^{\circ}\text{C}$	-	22	35	mA
		$V_R = 5\text{ V}; f = 1\text{ MHz}; T_j = 25\text{ }^{\circ}\text{C to } 125\text{ }^{\circ}\text{C}$	-	350	-	pF

Rectifier diodes  
Schottky barrier

PBYR1045 series

