

# IGBT Transistor

## **GT8Q102**

1200V / 8A

# DATASHEET

OEM – Toshiba


Source: Toshiba Databook 1995/96

## MAXIMUM RATINGS (Ta=25°C)


CHARACTERISTIC	SYMBOL	RATING	UNIT
Collector-Emitter Voltage	Vces	1200	V
Gate-Emitter Voltage	Vges	+/-20	V
Collector Current	DC	IC	8
	1ms	Icp	16
Collector Power Dissipation	Pc	50	W
Junction Temperature	Tj	150	°C
Storage Temperature Range	Tstg	-55~150	°C

Source: Toshiba IGBT Databook 95/96

## ELECTRICAL CHARACTERISTICS (Ta=25°C)

CHARACTERISTICS	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Gate Leakage Current	Iges	Uge=+/-20V, Vce=0	-	-	+10	uA
Collector Cut-off Current	Ices	Uce=1200V, Uge=0	-	-	1.0	mA
Gate-Emitter Cut-off Voltage	Uge (off)	Ic=8mA, Uce=5V	3.0	-	6.0	V
Collector-Emitter Saturation Voltage	Uce (sat)	Ic=8A, Uge=15V	-	3.0	4.0	V
Input Capacitance	Cies	Uce=10V, Uge=0, f=1MHz	-	1000	-	pF
Switching Time	Rise Time		-	0.30	0.60	uS
	Turn-on Time		-	0.40	0.80	
	Fall Time		-	0.25	0.50	
	Turn-off Time		-	0.70	1.30	

2-10S2C



EQUIVALENT CIRCUIT

